Product Bulletin
Cisco public

CISCO
The bridge to possible

Introducing 10/25G Industrial Temperature LR reach Transceiver

Contents

For more information

Error! Bookmark not defined.

PB2364785

Cisco is introducing an Industrial Temperature range, LR reach, Dual Rate Transceiver for Carrier Ethernet, Enterprise and Mobile fronthaul applications.

Table 1 shows 10/25G Industrial Temperature, LR reach transceiver PID.

Table 1. 10/25G Industrial Temperature LR reach Transceiver

Data Rate	Protocol	Receiver Electrical Interface	Reach	Temp. Range	PID
10 and 25G	Ethernet, CPRI and eCPRI	Limiting	10km*	Industrial	SFP-10/25G-LR-I=

^{*} Link distance of up to 15km are supported as engineered links as long as channel insertion loss is <9.3dB

For more information

25GBASE, SFP+ transceivers datasheets:

• Cisco Transceiver Modules - Cisco 25GBASE SFP28 Modules Data Sheet - Cisco

Compatibility information:

https://tmgmatrix.cisco.com/home

If you have further questions or suggestions, contact your local account representative.

Americas Headquarters Cisco Systems, Inc. San Jose, CA Asia Pacific Headquarters Cisco Systems (USA) Pte. Ltd. Singapore

Europe HeadquartersCisco Systems International BV Amsterdam,
The Netherlands

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at https://www.cisco.com/go/offices.

Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: https://www.cisco.com/go/trademarks. Third-party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1110R)

Printed in USA C25-2364785-00 06/21