

Asynchronous Terminal Server Interface Modules for Cisco 4000 Series Integrated Services Routers

Product overview

Asynchronous interface modules provide high-density terminal server functionality to Cisco® 4000 Series Integrated Services Routers (ISRs). Up to 200 terminal server connections can be supported on a single platform—eight more than are supported on the Cisco ISR G2.

Asynchronous interface modules are offered as both a Network Interface Module (NIM) and a high-density Service Module (SM) (Figure 1).

Table 1 lists the asynchronous NIM and SM SKUs.

Table 1. Cisco asynchronous interface modules for 4000 Series ISRs

SKU	Description	Supported interface
NIM-16A	16-Port Async Serial NIM	RS-232
NIM-24A	24-Port Async Serial NIM	RS-232
SM-X-64A	64-Port Async Serial SM	RS-232

Figure 1. Asynchronous interface modules for Cisco 4000 Series ISRs



Applications

These modules provide highly flexible connections that allow access to EIA-232 ports across a LAN or WAN.

The asynchronous interface modules for the 4000 Series ISRs are specifically designed for terminal server use. This capability allows for out-of-band management of console ports, giving the network operator full console access to a network of remote devices from a central location.

The asynchronous interface modules for the Cisco 4000 Series ISRs do not support Serial Line Internet Protocol (SLIP) or Point-to-Point Protocol (PPP). Asynchronous routing and data encapsulation features are thus not supported.

Platform support

The NIM-16A and NIM-24A are supported in the NIM slots of all 4000 Series ISR platforms, whereas the SM-X-64A is supported only on 4000 Series platforms with an SM-X slot.

Table 2 lists the platforms that support each asynchronous interface module type.

Table 2. Platform support

Module	Supporting platforms
NIM-16A	Cisco 4221, 4321, 4331, 4351, 4431, 4451
NIM-24A	Cisco 4221, 4321, 4331, 4351, 4431, 4451
SM-X-64A	Cisco 4331, 4351, 4451

The number of asynchronous interface modules supported on each platform is governed only by the number of available slots. A maximum terminal server port count of 200 is achieved in the 4351 and 4451 ISRs by combining three NIM-24A modules with two SM-X-64A modules.

Table 3 lists the maximum number of asynchronous interface modules per platform.

Table 3. Maximum number of asynchronous interface modules per ISR

Platform	NIM-16A	NIM-24A	Maximum NIMs	Maximum SM-X-64A
Cisco 4221, 4321	2	2	2	Not supported
Cisco 4331	2 (3 [*])	2 (3 [*])	2 (3 [*])	1
Cisco 4351, 4451	3 (5 [*])	3 (5 [*])	3 (5 [*])	2
Cisco 4431	3	3	3	Not supported

^{*} When using SM-X-NIM-ADPTR. One 16- or 24-port module is supported per adapter. The Cisco 4331 ISR supports one adapter. The Cisco 4351 and 4451 ISRs support two adapters. The maximum number of SM-X-64A modules in this table assumes that no SM-X-NIM-ADPTR is being used for NIMs.

Software requirements

Table 4 lists the minimum Cisco IOS[®] Software release required for each module.

Table 4. Minimum Cisco IOS Software release

Module	Minimum Cisco IOS Software release	Cisco IOS XE feature set
NIM-16A	16.3.1	IP Base and up
NIM-24A	16.3.1	IP Base and up
SM-X-64A	16.6.1	IP Base and up

Connectors and cabling

Asynchronous interface modules are connected to RS-232 ports on network devices with what is commonly called an "Octal cable." An Octal cable is an 8-port asynchronous cable consisting of an 8-port high-density connector fanning out into eight individual cables, each with an RJ-45 connector. Optional RJ-45- to DB-25 modular adapters are required when a conversion from RJ-45 to DB-25 is needed.

The 8-port connector is identical to the connector type used on the previous ISR platforms, and the asynchronous interface modules will thus support the use of the previous-generation asynchronous cable type CAB-HD8-ASYNC.

Table 5 lists the high-density 8-port EIA-232 asynchronous cables supported on the asynchronous interface modules.




Table 5. Cables supported on the asynchronous interface modules

Cable SKU	Description
CAB-HD8-ASYNC	Old generation for ISR G1 and G2
CAB-ASYNC-8	New generation; same connector and pin-out as CAB-HD8-ASYNC, but with slimmer housing

Due to the compact connector placement on the NIM-24A, only the new cable type CAB-ASYNC-8 with slimmer housing is supported in the lower and middle sockets. See Table 6.

Table 6 lists the cables supported by each module.

Table 6. Cables supported by modules

NIM-16A	NIM-24A	SM-X-64A
		
Upper socket: CAB-HD8-ASYNC or CAB-ASYNC-8	Upper socket: CAB-ASYNC-8 only	Upper sockets: CAB-HD8-ASYNC or CAB-ASYNC-8
–	Middle socket: CAB-ASYNC-8 only	–
Lower socket: CAB-HD8-ASYNC or CAB-ASYNC-8	Lower socket: CAB-HD8-ASYNC or CAB-ASYNC-8	Lower sockets: CAB-HD8-ASYNC or CAB-ASYNC-8

Connection rate

9600 baud is the generally recommended connection rate for all terminal server modules. Higher connection rates can be used for a low number of simultaneous connections.

Table 7 lists the recommended connection rate per module type.

Table 7. Recommended connection rates

Baud rate	NIM-16A and NIM-24A	SM-X-64A
9600	Recommended	Recommended
115200	Use only with a low number of simultaneous connections	Use only with a low number of simultaneous connections
230400	Not recommended	Not recommended

Supported command-line interface

When an asynchronous interface module is inserted into the router, Cisco IOS Software will automatically create an asynchronous interface based on the slot number. However, since only terminal server service is supported, any eventual configuration of network protocols will have no effect.

Common specifications

The specifications listed here are common to all serial and asynchronous modules.

Agency approvals:

- CAN/CSA 22.2 No. 60950-1-07, Second Edition (Canada)
- EN 60950-1: 2006 (European Union)
- UL 60950-1 (United States)
- IEC 60950-1: 2005 (international)

Immunity:

- CISPR24
- EN 300386
- EN55024
- KN35
- TCVN 7317

Emissions:

- FCC Part 15 Class A
- ICES-003 Class A
- EN55032 Class A
- CISPR32 Class A
- AS/NZS CISPR32
- VCCI Class A
- EN 300386
- EN61000-3-3
- EN61000-3-2
- KN 32: 2015
- TCVN 7189

Physical specifications:

- Single-wide NIM and SM-X modules, no slot restrictions
- Dimensions (NIM modules) (H x W x D): 1.25 x 3.5 x 6.7 in. / 32 x 89 x 172 mm
- Dimensions (SM-X-64A) (H x W x D): 1.58 x 8.1 x 9.2 in. / 40 x 206 x 233 mm

Environmental specifications:

- Operating temperature: 32° to 104°F (0° to 40°C)
- Storage temperature: -4° to 149°F (-20° to 65°C)
- Relative humidity: 10 to 90 percent, noncondensing

Cisco and partner services for the branch office

Services from Cisco and our certified partners can help you transform the branch-office experience and accelerate business innovation and growth in Cisco Enterprise Networks. We have the depth and breadth of expertise to create a clear, replicable, optimized branch-office footprint across technologies. Planning and design services align technology with business goals and can increase the accuracy, speed, and efficiency of deployment.

Technical services help improve operation efficiency, save money, and mitigate risk. Optimization services are designed to continuously improve performance and help your team succeed with new technologies.

For more information

For more information about Cisco Services, visit <https://www.cisco.com/go/services>.

For more information about Cisco 4000 Series ISRs, visit: <https://www.cisco.com/c/en/us/products/routers/4000-series-integrated-services-routers-isr/index.html>.

Cisco Capital

Financing to Help You Achieve Your Objectives

Cisco Capital can help you acquire the technology you need to achieve your objectives and stay competitive. We can help you reduce CapEx. Accelerate your growth. Optimize your investment dollars and ROI. Cisco Capital financing gives you flexibility in acquiring hardware, software, services, and complementary third-party equipment. And there's just one predictable payment. Cisco Capital is available in more than 100 countries. [Learn more](#).




Americas Headquarters
Cisco Systems, Inc.
San Jose, CA

Asia Pacific Headquarters
Cisco Systems (USA) Pte. Ltd.
Singapore

Europe Headquarters
Cisco Systems International BV Amsterdam,
The Netherlands

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at <https://www.cisco.com/go/offices>.

 Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: <https://www.cisco.com/go/trademarks>. Third-party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1110R)