Data sheet Cisco public CISCO
The bridge to possible

# Cisco UCS C240 M7 Rack Server

# Contents

Product overview	3
High performance for data-intensive applications	4
Product specifications	5
System requirements	6
Ordering information	6
Warranty information	6
Cisco support	7
Product sustainability	7
Product environmental information	7
Cisco and partner services	8
Cisco Capital	8
Document history	9

The Cisco UCS° C240 M7 Rack Server delivers industry-leading performance and expandability.

#### Product overview



The Cisco UCS C240 M7 Rack Server is well-suited for a wide range of storage and I/O-intensive applications such as big data analytics, databases, collaboration, virtualization, consolidation, and high-performance computing in its two-socket, 2RU form factor.

The Cisco UCS C240 M7 Rack Server extends the capabilities of the Cisco UCS rack server portfolio. It incorporates the 4<sup>th</sup> or 5<sup>th</sup> Gen Intel® Xeon® Scalable Processors with 60 percent more cores per socket advanced features like Intel Advanced Matrix Extensions (AMX), Data Streaming Accelerator (DSA), In-Memory Analytics Accelerator (IAA), and QuickAssist Technology (QAT), many applications will see significant performance improvements.

You can deploy the Cisco UCS C-Series rack servers as standalone servers or as part of the Cisco Unified Computing System™ managed by Cisco Intersight™ or Cisco UCS Manager¹ to take advantage of Cisco® standards-based unified computing innovations that can help reduce your Total Cost of Ownership (TCO) and increase your business agility.

The Cisco UCS C240 M7 Rack Server brings many new innovations to the UCS rack server portfolio. With the introduction of PCIe Gen 5.0 expansion slots for high-speed I/O, a DDR5 memory bus, and expanded storage capabilities, the server delivers significant performance and efficiency gains that will improve your application performance. Its features including the following:

- Supports up to two 4<sup>th</sup> or 5<sup>th</sup> Gen Intel Xeon Scalable CPU, with up to 64 cores per socket
- Up to 32 DDR5 DIMMs for up to 8 TB of capacity using 256 GB DIMMs (16 DIMMs per socket)
- Up to 5600 MT/s DDR5 memory plus other speeds depending on the CPU installed
- Up to 8 PCle 4.0 slots or up to 4 PCle 5.0 slots, plus a hybrid modular LAN on motherboard (mLOM) /OCP 3.0 slot
- Support for Cisco UCS VIC 15000 Series adapters as well as third-party options
- Up to 28 hot-swappable Small-Form-Factor (SFF) SAS/SATA or NVMe drives (with up to 8 direct-attach NVMe drives)
  - New tri-mode RAID controller supports SAS4 plus NVMe hardware RAID
  - Option for 28 NVMe drives at PCle Gen4 x2 each

- M.2 boot options
  - Up to two 960GB SATA M.2 drives with hardware RAID, or
  - Up to two 960GB NVMe M.2 drives with NVMe hardware RAID
- · Up to eight GPUs supported
- Modular LOM / OCP 3.0
  - One dedicated PCle Gen4x16 slot that can be used to add an mLOM or OCP 3.0 card for additional rear-panel connectivity.
  - mLOM slot that can be used to install a Cisco UCS Virtual Interface Card (VIC) without consuming a PCle slot, supporting quad port 10/25/50 Gbps or dual port 40/100/200 Gbps network connectivity
  - OCP 3.0 slot features full out-of-band management for select adapters

#### High performance for data-intensive applications

The Cisco UCS C240 M7 Rack Server is well suited for a wide range of enterprise workloads, including:

- · Big data and analytics
- Collaboration
- Small and medium-sized business databases
- · Virtualization and consolidation
- Storage servers
- High-performance appliances

Cisco UCS C240 M7 Rack Servers can be deployed as standalone servers, part of a Cisco UCS-managed environment, or through Cisco Intersight. When used in combination with Cisco Intersight, the C240 M7 brings the power and automation of unified computing to enterprise applications, including Cisco SingleConnect technology, drastically reducing switching and cabling requirements.

Cisco Intersight leverages the familiar capabilities of UCS Manager with service profiles, templates, and policy-based management to enable rapid deployment and help ensure deployment consistency. It also enables end-to-end server visibility, management, and control in both virtualized and bare-metal environments.

The Cisco Integrated Management Controller (IMC) delivers comprehensive out-of-band server management with support for many industry standards, including:

- Redfish Version 1.13.0 (2021.1 schema0)
- Intelligent Platform Management Interface (IPMI) v2.0
- Simple Network Management Protocol (SNMP) v2 and v3
- Syslog
- Simple Mail Transfer Protocol (SMTP)

- Key Management Interoperability Protocol (KMIP)
- cKVM (all-new Cisco KVM)
- Command-Line Interface (CLI)
- XML API

Management Software Development Kits (SDKs) and DevOps integrations exist for Python, Microsoft PowerShell, Ansible, Puppet, Chef, and more. For more information about integrations, see Cisco DevNet (<a href="https://developer.cisco.com/site/ucs-dev-center/">https://developer.cisco.com/site/ucs-dev-center/</a>).

## Product specifications

Table 1 lists the specifications for the Cisco UCS C240 M7 Rack Server.

Table 1. Specifications

Table 1. Specifications		
Item	Specifications	
Form factor	2RU rack server	
Processors	Up to 2x 5th Gen Intel Xeon Scalable processors (1 or 2) or Up to 2x 4th Gen Intel Xeon Scalable processors (1 or 2)	
Memory	32 DDR5-5600 DIMM slots (16 DIMMS per CPU): 16, 32, 48, 64, 96, 128, 256GB at up to 5600 MT/s for up to 8TB of memory with 5th Gen Intel Xeon Scalable processors or 32 DDR5-4800 DIMM slots (16 DIMMS per CPU): 16, 32, 64, 128, 256GB at up to 4800 MT/s for up to 8TB of memory with 4th Gen Intel Xeon Scalable processors	
PCIe expansion	Up to 8 PCle 4.0 slots or up to 4 PCle 5.0 slots plus 1 dedicated 24-Gbps RAID controller slot and 1 dedicated mLOM slot	
RAID controllers	<ul> <li>Internal controllers:</li> <li>24-Gbps modular tri-mode controller supports SAS 4 or NVMe hardware RAID</li> <li>Cisco 12-Gbps modular RAID controller (PCle 4.0) with 4-GB Flash-Backed Write Cache (FBWC), or</li> <li>Cisco 12-Gbps modular SAS Host Bus Adapter (HBA)</li> <li>External controller: Cisco 12-Gbps 9500-8e SAS HBA</li> </ul>	
Internal storage	Backplane options:  • Up to 28 x 2.5-inch SAS and SATA HDDs/ SSDs and NVMe SSDs (up to 8 NVMe direct attach)  • Up to 28 x 2.5-inch NVMe PCle SSDs (all direct-attach Gen4 x2)	
mLOM/OCP 3.0	One dedicated socket (x16 PCle lane) that can be used to add an mLOM or OCP 3.0 card for additional rear-panel connectivity.  • mLOM slot can flexibly accommodate 10/25/50 and 40/100/200 100-Gbps Cisco VIC adapters.  • OCP 3.0 slot features full out-of-band manageability that supports Intel X710 OCP Dual 10GBase-T via mLOM interposer.	

Item	Specifications	
Power supplies	Hot-pluggable, redundant platinum and titanium options:  • Platinum: 1050W DC, and 1600W AC  • Titanium: 1200W AC, and 2300W AC	
Other storage	<ul> <li>Dedicated Baseboard Management Controller (BMC) FlexMMC for utilities (on board)</li> <li>Dual M.2 SATA/NVMe SSDs with HW RAID support</li> </ul>	
Management	<ul> <li>Cisco Intersight</li> <li>Cisco Integrated Management Controller (IMC)</li> <li>Cisco UCS Manager</li> </ul>	
Rack options	Cisco ball-bearing rail kit with optional reversible cable management arm	
Hardware and software interoperability	See the <u>Cisco Hardware and Software Interoperability List</u> for a complete listing of supported operating systems and peripheral options.	

### System requirements

Table 2 lists system requirements for the server.

 Table 2.
 System requirements

Item	Requirements
Cisco IMC	Release 4.3(1) or later

# Ordering information

Table 3. Ordering Information

Part #	Product description
UCSC-C240-M7SX	C240 M7 2RU standard server with up to 28x SFF drive bays
UCSC-C240-M7SN	C240 M7 2RU NVMe optimized server with up to 28x NVMe drive capability

For information about installing or upgrading your server, see the <u>Cisco UCS C240 M7 Server Installation and Service Guide</u>.

For ordering information, see Cisco UCS C240 M7 SFF rack server specifications sheet

# Warranty information

The Cisco UCS C240 M7 Rack Server has a three-year, Next-Business-Day (NBD) hardware warranty and a 90-day software warranty.

#### Cisco support

Augmenting the Cisco Unified Computing System (Cisco UCS) warranty, Cisco Smart Net Total Care® and Cisco Solution Support services are part of Cisco's technical services portfolio. Smart Net Total Care combines Cisco's industry-leading and award-winning foundational technical services with an extra level of actionable business intelligence that is delivered to you through the smart capabilities in the Smart Net Total Care portal. Learn more about Smart Net Total Care.

Cisco Solution Support includes both Cisco product support and solution-level support, resolving complex issues in multivendor environments on average 43 percent more quickly than with product support alone. Cisco Solution Support is a critical element in data center administration, helping to rapidly resolve any issue encountered while maintaining performance, reliability, and return on investment.

This service centralizes support across your multivendor Cisco environment for both our products and solution partner products that you have deployed in your ecosystem. Whether there is an issue with a Cisco product or with a solution partner product, just call us. Our experts are the primary point of contact and own the case from first call to resolution. Learn more about <u>Cisco Solution Support</u>.

#### Product sustainability

Information about Cisco's Environmental, Social, and Governance (ESG) initiatives and performance is provided in Cisco's Corporate Social Responsibility (CSR) and sustainability reporting.

Table 4. Cisco environmental sustainability information

Sustainability top	ic	Reference
General	Information on product-material-content laws and regulations	<u>Materials</u>
	Information on electronic waste laws and regulations, including our products, batteries, and packaging	WEEE compliance
	Information on our product takeback and reuse program	Cisco Takeback and Reuse Program
	Sustainability inquiries	Contact: csr_inquiries@cisco.com
	Operating and non-operating conditions	Product specifications
Material	Product packaging weight and materials	Contact: environment@cisco.com

#### Product environmental information

Product environmental information for users per Commission Regulation (EU) 2019/424 <a href="https://www.cisco.com/web/dofc/23906226.pdf">https://www.cisco.com/web/dofc/23906226.pdf</a>.

#### Cisco and partner services

Cisco and our industry-leading partners deliver services that can accelerate your transition to a Cisco UCS X-Series Modular System solution. Cisco Unified Computing Systems Services can help you create an agile infrastructure, accelerate time to value, reduce costs and risks, and maintain availability during deployment and migration. After deployment, our services can help you improve performance, availability, and resiliency as your business needs evolve and help you further mitigate risk. For more information, visit <a href="https://www.cisco.com/go/unifiedcomputingservices">https://www.cisco.com/go/unifiedcomputingservices</a>.

#### Cisco Capital

#### Flexible payment solutions to help you achieve your objectives

Cisco Capital® makes it easier to get the right technology to achieve your objectives, enable business transformation, and help you stay competitive. We can help you reduce the total cost of ownership, conserve capital, and accelerate growth. In more than 100 countries, our flexible payment solutions can help you acquire hardware, software, services, and complementary third-party equipment in easy, predictable payments. Learn more.

# Document history

New or revised topic	Described in	Date
Support for 5 <sup>th</sup> Gen Intel® Xeon® Scalable Processors with 5600MT/s DDR5	Product Specifications	December 14, 2023

Americas Headquarters Cisco Systems, Inc. San Jose, CA Asia Pacific Headquarters Cisco Systems (USA) Pte. Ltd. Singapore **Europe Headquarters**Cisco Systems International BV Amsterdam,
The Netherlands

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at https://www.cisco.com/go/offices.

Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: https://www.cisco.com/go/trademarks. Third-party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1110R)

Printed in USA C78-3387774-04 01/24