

# Cisco ATA 190 Analog Telephone Adaptor

## Product Overview

The Cisco® ATA 190 Analog Telephone Adaptor is a handset-to-Ethernet adaptor that turns traditional telephone devices into IP devices (Figures 1 and 2). Customers can take advantage of the many new and exciting IP telephony applications by connecting their analog devices to Cisco ATAs.

The Cisco ATA products are standards-based communication devices that deliver true, next-generation voice-over-IP (VoIP) terminations to businesses and residences worldwide. The Cisco ATA 190:

- Protects existing telephone investment: The Cisco ATA 190 supports two voice ports (RJ-11 phone ports), each with its own independent telephone number, and a single RJ-45 10/100 BASE-T Ethernet port. Each port supports either voice calls or fax sessions, and both ports can be used simultaneously. This adaptor can use existing Ethernet LAN deployments.
- Is cost-effective: The Cisco ATA 190 helps customers turn their analog phone devices into IP devices cost-effectively and is the preferred solution to address the needs of customers who connect to enterprise networks, small-office environments, or the emerging VoIP managed voice services and local services market.

Enterprise customers can use the Cisco ATA 190 to connect analog phones and fax machines to their VoIP network. Service providers are taking advantage of emerging telephony applications and the ease of deploying second-line services using the Cisco ATA solutions.

**Figure 1.** Cisco ATA 190 Endpoint (Top View)



**Figure 2.** Cisco ATA 190 (Rear View)



## Features and Benefits

Table 1 lists the features and benefits of the Cisco ATA 190.

**Table 1.** Features and Benefits of Cisco ATA 190

Feature	Benefits
<b>Configuration and Provisioning</b> <ul style="list-style-type: none"> <li>Configuration as per Cisco endpoints devices</li> <li>Autoprovisioning with Trivial File Transfer Protocol (TFTP) for servers</li> <li>Automatic assignment of IP address, network routing IP, and subnet mask using Dynamic Host Configuration Protocol (DHCP)</li> <li>Touch-tone telephone keypad configuration with voice prompt</li> <li>Administration password to protect configuration and access</li> <li>Remote upgrades through network</li> </ul>	<ul style="list-style-type: none"> <li>Cisco Unified Communications Manager (UCM) standard configuration and provisioning options</li> <li>Ease of administration</li> </ul>
<b>Voice Quality</b> <ul style="list-style-type: none"> <li>Advanced preprocessing to optimize full-duplex voice compression</li> <li>High-performance line-echo cancellation to eliminate noise and echo</li> <li>Voice activity detection (VAD) and comfort noise generation (CNG) to save bandwidth by delivering voice, not silence; VAD is configurable, and the ATA 190 determines whether CNG should be turned on dynamically</li> <li>Dynamic network monitoring to reduce jitter artifacts such as packet loss</li> </ul>	Clear, natural-sounding voice quality
<b>Signaling Protocol</b> <ul style="list-style-type: none"> <li>Session Initiation Protocol (SIP) on the Cisco line side</li> </ul>	Allows interoperation with Cisco UCM SIP solution
<b>Security</b> <ul style="list-style-type: none"> <li>Secure Real-Time Transfer Protocol (SRTP) and Transport Layer Security (TLS) over SIP</li> </ul>	Secure media and secure signaling support, for secure solutions
<b>Fax Support</b> <ul style="list-style-type: none"> <li>T38 fax support</li> </ul>	Standard fax capability to send faxes over the IP network; the T.38 fax relay feature enables devices to use fax machines to send files over the IP network
<b>Form Factor</b> <ul style="list-style-type: none"> <li>Fits in most environments</li> </ul>	New form-factor design based on the Cisco endpoints portfolio

## Cisco UCM Version Compatibility

The Cisco ATA 190 is compatible with Cisco UCM Versions 8.5(1), 8.6(2), 9.1(2), 10.0(1) and later.

## Product Specifications

Table 2 gives specifications of the Cisco ATA 190.

**Table 2.** ATA 190 Product Specifications

Physical Specifications	
<b>Power</b>	Power supply: Universal AC power supply 100 and 240V DC input voltage: 5 VDC at 2.0A maximum power consumption: 5W
<b>Noise level</b>	Less than 34 dBA at 3 ft (0.91m)
<b>Connectors</b>	2 RJ-11
<b>Thermal</b>	32 to 113°F (0 to 45°C) -77 to 158°F (-25 to 70°C)
<b>Humidity</b>	Operating humidity: 0 to 90% noncondensing Storage humidity: 10 to 90% noncondensing
<b>Mean time between failure (MTBF)</b>	100,000 hours

Physical Specifications	
<b>Physical dimensions (H x W x D) and weight</b>	3.98 x 3.98 x 1.10 in. (101 x 101 x 28 mm) Unit weight: 5.40 oz (153g)
<b>Compliance</b>	FCC (Part 15 Class B), CE, ICES-003, A-Tick certification, Restriction of Hazardous Substances (RoHS), and UL

Software Specifications	
<b>Configurable tones</b>	Configurable for two sets of frequencies and single set of on/off cadence
<b>Dual-tone multi-frequency (DTMF)</b>	DTMF tone detection and generation
<b>Fax</b>	Fax pass-through and T.38 fax relay mode Enhanced fax pass-through is supported on the Cisco ATA. Fax transmission rate is up to 14 kbps in T38 mode and 34 kbps in fax pass-through mode. The rate is not configurable, and the Cisco ATA 190 autonegotiates and chooses the maximum rate.
<b>Line-echo cancellation</b>	<ul style="list-style-type: none"> <li>Echo canceller for each port</li> <li>Double-talk detection</li> </ul>
<b>Out-of-band DTMF</b>	RFC 2833 <b>Note:</b> You cannot transmit RFC 2833 and in-band signaling simultaneously.
<b>Configuration</b>	<ul style="list-style-type: none"> <li>DHCP (RFC 2131)</li> <li>Web configuration through built-in web server</li> <li>Touch-tone phone keypad configuration with voice prompt</li> <li>Basic boot configuration (RFC 1350 TFTP Profiling) by touch-tone phone keypad or built-in web server</li> <li>Dial-plan configuration through Cisco UCM</li> <li>Cisco Discovery Protocol through Cisco UCM</li> </ul>
<b>Quality of service (QoS)</b>	<ul style="list-style-type: none"> <li>Class-of-service (CoS) bit-tagging (802.1P)</li> <li>Type-of-service (ToS) bit-tagging</li> </ul>
<b>Security</b>	Encrypted TFTP configuration files
<b>Voice coders-decoders (codecs)</b>	<ul style="list-style-type: none"> <li>G.729A and G.729AB</li> <li>G.711 a-law</li> <li>G.711 mu-law</li> </ul>
<b>Voice features</b>	<ul style="list-style-type: none"> <li>VAD</li> <li>CNG</li> <li>Dynamic jitter buffer (adaptive)</li> </ul>
<b>VoIP protocols</b>	SIP

## Warranty Information

Find warranty information on Cisco.com at the [Product Warranties](#) page.

## Ordering Information

To place an order, visit the [Cisco Ordering homepage](#) and refer to Table 3. To download software, visit the [Cisco Software Center](#).

**Table 3.** Ordering Information

Product Name	Part Number
Cisco ATA 190	ATA190

---

## Cisco Services

Cisco Services integrates closely with consumer marketing teams as an essential element of any technology solution. Please contact your Cisco Services marketing communications manager if you have not already received targeted services content blocks for integration. Please send an email message to [ca-marcom@cisco.com](mailto:ca-marcom@cisco.com) if you are not sure of the appropriate contact.

Cisco Services makes networks, applications, and the people who use them work better together.

Today, the network is a strategic platform in a world that demands better integration between people, information, and ideas. The network works better when services, together with products, create solutions aligned with business needs and opportunities.

The unique Cisco Lifecycle approach to services defines the requisite activities at each phase of the network lifecycle to help ensure service excellence. With a collaborative delivery methodology that joins the forces of Cisco, our skilled network of partners, and our customers, we achieve the best results.

## For More Information

For more information about the Cisco ATA 190, contact your local Cisco account representative.



---

Americas Headquarters  
Cisco Systems, Inc.  
San Jose, CA

Asia Pacific Headquarters  
Cisco Systems (USA) Pte. Ltd.  
Singapore

Europe Headquarters  
Cisco Systems International BV Amsterdam,  
The Netherlands

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at [www.cisco.com/go/offices](http://www.cisco.com/go/offices).

Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: [www.cisco.com/go/trademarks](http://www.cisco.com/go/trademarks). Third party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1110R)