

Cisco RF Gateway 10 Supervisor Engine 7-E

Product Overview

The Cisco® RF Gateway 10 Supervisor Engine 7-E (Figure 1) for the Cisco RF Gateway 10 universal edge quadrature amplitude modulation (U-EQAM) modulator redefines the way aggregation and traffic management features are managed at the edge of the cable network. Specially optimized for the Cisco RF Gateway 10 platform, the supervisor engine can be deployed in a redundant configuration with automatic failover. It runs the comprehensive feature set available in Cisco IOS® XE Software Release 3.2.0 SQ, with an array of management, line-rate Ethernet aggregation and switching, and packet filtering functions—all embedded in the carrier-class Cisco RF Gateway 10 platform. The Cisco RF Gateway 10 Supervisor Engine 7-E provides the increased switching and processing performance required for the new high-density Cisco RF Gateway Downstream 384 (RFGW-DS384) Universal Edge QAM Line Card.

Figure 1. Cisco RF Gateway 10 Supervisor Engine 7-E



Before, switches and routers had to be externally connected to edge QAM modulators and configured separately to manage them. As separate elements, switches and routers and edge QAM modulators provided limited management functionality, and the result has been less-scalable edge solutions. Now, with the integrated Cisco RF Gateway 10 Supervisor Engine 7-E, the intelligence of the Cisco IP Next-Generation Network (IP NGN) is available for more efficient and scalable packet forwarding and management of line cards in the gateway.

Management of data and video traffic can be split into data plane and control plane processing. The data plane manages the aggregation and forwarding of multiple services to the edge QAM resources (for example, Ethernet switching, routing, aggregation, and filtering). Interactions with control interfaces for video and DOCSIS® are managed by the control plane (for example, setup and teardown of video sessions, creation of voice-over-IP [VoIP] calls, management of high-speed data services, and management of the distribution of packets and environmental factors in the gateway). The aggregation management utility in the supervisor engine allows cable operators to extract detailed information from a single line card on the overall operational status of the entire gateway.

Features and Benefits

Table 1 lists the features and benefits of the Cisco RF Gateway 10 Supervisor Engine 7-E.

Table 1. Features and Benefits

Feature	Benefit
250 Mpps and 848 Gbps total switching capacity	Ethernet aggregation for edge QAM applications can be conducted directly on the supervisor of the Cisco RF Gateway 10, thus saving rack space, reducing the total number of boxes in the network, and providing network architectural flexibility.
Four integrated 10 Gigabit Ethernet or 1 Gigabit Ethernet Enhanced Small Form-Factor Pluggable (SFP+) ports	Flexible uplink connections accommodate multiple customer network architectures.
Supervisor redundancy support	Carrier-class high-availability performance.
Supervisor design from Cisco Catalyst® Series switch supervisor family	Comprehensive feature set from parent platform includes Layer 2 switching, Layer 3 routing, advanced security, and IPv6 support. Continual expansion of feature set from parent platform, with future hardware and software roadmap.
Distributed architecture with control plane terminations on supervisor and data plane terminations on RF line cards	Advanced management of control and data plane processing optimizes performance, high-availability switchover times, resource utilization, and operational efficiencies.
Operates Cisco IOS XE Software Release 3.2.0 SQ	Common and customized service provider feature set across high-end Cisco switches and routers that can take advantage of the multicore CPU architecture of the next-generation Cisco Supervisor 7-E. Support for end-to-end advanced networking architectures with functional compatibility.

Product Specifications

Table 2 lists the hardware specifications for the Cisco RF Gateway 10 Supervisor Engine 7-E.

Table 2. Product Specifications

Specification	Value
Physical	Occupies a single supervisor slot in the Cisco RF Gateway 10 chassis
Weight	5.5 lbs (2.5 kg)
Environmental	Operating altitude: -60 to 3000 m Storage temperature: -40 to 167°F (-40 to 75°C) Operating temperature: 32 to 104°F (0 to 40°C) Relative humidity: 10% to 90%, noncondensing
LEDs	System status: green (operational); red (faulty) Switch utilization load: 1% to 100% aggregate switching usage
Console port	RJ-45 female
Management port	10/100 BASE-TX Ethernet
Reset button	Switch recess protected
Synchronous Dynamic RAM (SDRAM)	2 GB upgradable to 4 GB
Ethernet Uplink Interfaces	
Dual supervisors operating in active/standby redundancy mode	Up to four Gigabit Ethernet or two 10 Gigabit Ethernet per chassis
Single supervisor operating in nonredundant mode	Up to four Gigabit Ethernet or two 10 Gigabit Ethernet per chassis
Small Form Factor Pluggables Supported	
Gigabit Ethernet interfaces	SFP-GE-S, SFP-GE-S, SFP-GE-L
10 Gigabit Ethernet interfaces	SFP-10G-SR, SFP-10G-LR

The Cisco RF Gateway 10 Supervisor Engine 7-E has a very high-performance Ethernet switching feature set. Advanced traffic management features include:

- Quality of service (QoS)
- Virtual LANs (VLANs)
- Multiple traffic queuing techniques such as IP differentiated services code points (DSCPs)
- Full-featured traffic classification, marking, and policing

Table 3 lists the software specifications for the Cisco RF Gateway 10 Supervisor Engine 7-E.

Table 3. Software Specifications

Specification	Value
Total centralized switching capacity	848 Gbps
Throughput	<ul style="list-style-type: none"> • 250 Mpps for IPv4 • 125 Mpps for IPv6
IPv4 routing entries	256,000
IPv4 routing entries	128,000
Switched Port Analyzer (SPAN)	<ul style="list-style-type: none"> • Maximum of 8 sessions: ingress and/or egress • SPAN port permits traffic monitoring of a single port, a group of ports, or the entire switch from a single network analyzer or Remote Monitoring (RMON) probe
High-Availability Features	
High-availability software features	<ul style="list-style-type: none"> • Route Processor Redundancy (RPR): warm reboot, nonstateful, line card reset • Open Shortest Path First (OSPF) fast convergence: incremental shortest path first (SPF) and link-state advertisement (LSA) throttling • Cisco Nonstop Forwarding (NSF) and Stateful Switchover (SSO) offer continuous packet forwarding during supervisor-engine switchover. Information is fully synchronized between supervisor engines to allow the standby supervisor engine to immediately take over in subsecond time if the primary engine fails • 1:N RF line card redundancy management • Comprehensive roadmap of enhanced high-availability features in future software releases including In Service Software Upgrade (ISSU)
Multicast Features	
Combination of base Cisco IOS multicast feature set and enhanced edge QAM multicast functionality.	
Multicast	<ul style="list-style-type: none"> • IP multicast routing protocols: Protocol Independent Multicast (PIM), including sparse mode and dense mode • Source Specific Multicast (SSM) and Any Source Multicast (ASM) • Internet Group Management Protocol (IGMP)
Multicast routes	32,000
Maximum unique video multicast sessions	2048 load-balanced sessions
Security Features	
The Cisco RF Gateway 10 Supervisor Engine 7-E has a strong contingent of security features, including TACACS+, Secure Shell (SSH) Protocol, and RADIUS, which provide centralized control of the switch and restrict unauthorized users from altering the configuration; standard and extended ACLs on all ports; 802.1X user authentication and accounting; and Unicast MAC filtering.	
Control plane policing	In hardware
Layer 2 Switching and Layer 3 Routing Features	
The substantial Cisco IOS portfolio of switching and routing features includes high-performance hardware-based packet forwarding, a full suite of VLAN features, IPv4, EIGRP, OSPF, IS-IS, RIP, RIP2, and BGP routing protocols, UniDirectional Link Routing (UDLR), and Layer 2 Tunneling Protocol (L2TP).	

Table 4 lists the management features of the Cisco RF Gateway 10 Supervisor Engine 7-E.

Table 4. Management

Platform Management and SNMP Features	
Comprehensive set of management functions for provisioning and for maintaining and resolving faults	<ul style="list-style-type: none"> • Single console port and single IP address to manage all system features • Software configuration management, including local and remote storage • Optional Secure Digital and Universal Serial Bus (USB) memory to store software images for backup and easy software upgrades • Simple Network Management Protocol (SNMP) v1, v2, and v3 instrumentation, delivering comprehensive in-band management • Command-line interface (CLI)-based management console to provide detailed out-of-band management • Show commands for granular monitoring and troubleshooting • Cisco NetFlow statistics • Cisco Discovery Protocol v1, v2 • Network Timing Protocol • Layer 2 traceroute • SNMP MIBs: <ul style="list-style-type: none"> ◦ Cisco Network Element Management 1.3 compliance ◦ IF-MIB ◦ ENTITY-MIB ◦ DOCS-IF-MIB ◦ DOCS-IF-MCMTS-MIB ◦ DOCS-CABLE-DEVICE-MIB ◦ DTI-MIB ◦ SCTE HMS Video MIB ◦ SCTE HMS QAM MIB

Regulatory Compliance

Table 5 gives compliance and emissions figures for the Cisco RF Gateway 10 and its components.

Table 5. Compliance and Emissions for the Cisco RF Gateway 10

Specification	Value
Network Equipment Building Standards (NEBS)/European Telecommunications Standards Institute (ETSI)	UL 60950CAN/CSA-C22.2 No. 60950, EN 60950, IEC 60950, TS 001, AS/NZS 3260
Electromagnetic compatibility (EMC)	FCC Part 15 (CFR 47) Class A, ICES-003 Class A, EN55022 Class A, AS/NZS CISPR22 Class A, AS/NZS 3548 Class A, VCCI Class A, ETS 300 386, EN 55022, KN22, EN 61000-3-2, EN 61000-3-3
Electromagnetic interference (EMI)	EN550082-1, EN55024, EN61000-4-2, EN61000-4-3, EN61000-4-5, EN61000-4-6, EN61000-4-8, EN61000-4-11, EN61000-6-1
Safety	GR-1089-Core Level 3, ETS 300 019 Storage Class 1.1, ETS 300 019 Transportation Class 2.3 (pending), ETS 300 019 Stationary Use Class 3.1, ETS 300 386
Restriction of Hazardous Substances (RoHS) compliance	ROHS5
Industry EMC, safety, and environmental standards	Designed to meet NEBS standard GR-63-Core and GR-1089-Core
Other industry standards	Cisco corporate compliance standards

System Requirements

Table 6 lists the system requirements for the Cisco RF Gateway 10 Supervisor Engine 7-E.

Table 6. System Requirements for the RF Gateway 10 Supervisor Engine 7-E

Chassis	Cisco RF Gateway 10 (RFGW-10)
Software	Cisco IOS XE Modular Software Release 3.2.0 SQ

Ordering Information

Table 7 gives ordering information for the Cisco RF Gateway 10 Supervisor Engine 7-E. To place an order, visit the [Cisco Ordering Homepage](#). To download software, visit the [Cisco Software Center](#).

Table 7. Ordering Information for the RF Gateway 10 Supervisor Engine 7-E

Product	Product Number	Product Description
Cisco RFGW Series Supervisor 7-E	RFGW-X45-SUP7-E	RFGW Supervisor 7-E, 4xSFP+ (10/1GE)
	RFGW-X45-SUP7-E=	RFGW Supervisor 7-E, 4xSFP+ (10/1GE) Spare
Cisco RFGW Series Supervisor memory options	SD-X45-2GB-E	Catalyst 4500 2GB SD Memory Card for Sup7-E
	USB-X45-4GB-E	Catalyst 4500 4GB USB device for Sup7-E
Cisco RFGW Series transceiver modules	SFP-GE-T	1000BASE-T SFP (NEBS 3 ESD)
	SFP-GE-S	1000BASE-SX SFP (DOM)
	SFP-GE-L	1000BASE-LX/LH SFP (DOM)
	SFP-10G-SR	10GBASE-SR SFP Module
	SFP-10G-LR	10GBASE-LR SFP Module
Cisco RFGW Series spares and accessories	RFGW-SUP-COVER	RFGW Supervisor slot cover
	RFGW-SUP-COVER=	RFGW Supervisor slot cover spare

Service and Support

Using the Cisco lifecycle services approach, Cisco and its partners provide a broad portfolio of end-to-end services and support that can help increase your network's business value and return on investment. This approach defines the minimum set of activities needed, by technology and by network complexity, to help you successfully deploy and operate Cisco technologies and optimize their performance throughout the lifecycle of your network.

For More Information

For more information about the Cisco RF Gateway 10 Supervisor Engine 7-E, visit <http://www.cisco.com/en/US/products/ps8360/index.html> or contact your local account representative.



Americas Headquarters
Cisco Systems, Inc.
San Jose, CA

Asia Pacific Headquarters
Cisco Systems (USA) Pte. Ltd.
Singapore

Europe Headquarters
Cisco Systems International BV Amsterdam,
The Netherlands

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at www.cisco.com/go/offices.

Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: www.cisco.com/go/trademarks. Third party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1110R)