

Release Notes for Cisco UCS E-Series Servers and the Cisco UCS E-Series Network Compute Engine, BIOS Releases UCSEM3_3.02 and UCSEDM3_3.02

First Published: 2022-01-07

Release Notes for Cisco UCS E-Series Servers and the Cisco UCS E-Series Network Compute Engine, BIOS Releases UCSEM3_3.02 and UCSEDM3_3.02

This document provides new features, system requirements, compatibility information, and open and resolved caveats for the Cisco UCS E-Series Server and the Cisco UCS E-Series Network Compute Engine (NCE) software, BIOS release UCSEDM3_3.02. Use this document in conjunction with the documents in the [Related Documentation, on page 6](#).



Note The UCSEDM3_3.02 applies only to the UCS-E180D-M3 and UCS-E1120D-M3 modules. The UCSEM3_3.02 applies only to the UCS-E160S-M3 module.



Note Documentation is sometimes updated after original publication; therefore, for updated content, review the documentation on Cisco.com.

Overview

The Cisco UCS E-Series Servers (E-Series Servers) and the Cisco UCS E-Series Network Compute Engine (NCE) are a family of size-, weight-, and power-efficient blade servers that are housed within the Cisco ISR 4000 series. These servers provide a general-purpose compute platform for branch-office applications deployed either as bare-metal on operating systems, such as Microsoft Windows or Linux, or as virtual machines on hypervisors, such as VMware vSphere Hypervisor, Microsoft Hyper-V, or Citrix XenServer.

The E-Series Servers are purpose-built with powerful Intel Xeon processors for general-purpose compute. They come in the following form factors: single-wide and double-wide. The single-wide E-Series Server fits into one server module (SM) slot, and the double-wide E-Series Server fits into two SM slots.



Note M3 servers are supported on the Cisco ISR 4000 series only.

System Requirements

Hardware Requirements



Note E-Series Servers and the SM E-Series NCE can be installed in the Cisco ISR G2 and the Cisco ISR 4000 series.

- The EHWIC E-Series NCEs are not supported from CIMC release 3.2.x.
- The NIM E-Series NCE can be installed in the Cisco ISR 4000 series only.

The following M3 E-Series Servers are supported:

- UCS-E160S-M3—Single-wide E-Series Server, 6-cores CPU, 1.9 -GHz clock speed
- UCS-E180D-M3—Double-wide E-Series Server, 8-cores CPU, 2.0 -GHz clock speed
- UCS-E1120D-M3—Double-wide E-Series Server, 12-cores CPU, 1.5 -GHz clock speed



Note The M2 and M3 E-Series Servers naming terminology indicates different generations of Intel processors within the respective servers.

The following NIM E-Series NCE is supported:

- UCS-EN140N-M2—NIM E-Series NCE, 4-cores CPU, 1.7-GHz clock speed



Note For details about the M2 and M3 E-Series Servers and the EHWIC E-Series NCE hardware, see the “Hardware Requirements” section in the [Cisco UCS E-Series Servers and the Cisco UCS E-Series Network Compute Engine Hardware Installation Guide](#) .

Software Requirements

E-Series Servers require three major software systems:

CIMC Firmware

Cisco Integrated Management Controller (CIMC) is a management module, which is built into the motherboard. A dedicated ARM-based processor, separate from the main server CPU, runs the CIMC firmware. The system ships with a running version of the CIMC firmware. You can update the CIMC firmware, but no initial installation is needed.

CIMC is the management service for the E-Series Servers. CIMC runs within the server. You can use CIMC to access, configure, administer, and monitor the server.

BIOS Firmware

BIOS initializes the hardware in the system, discovers bootable devices, and boots them in the provided sequence. It boots the operating system and configures the hardware for the operating system to use. BIOS manageability features allow you to interact with the hardware and use it. In addition, BIOS provides options to configure the system, manage firmware, and create BIOS error reports. The system ships with a running version of the BIOS firmware. You can update the BIOS firmware, but no initial installation is needed.



Note Table below lists the minimum BIOS versions required to use with CIMC 3.2.x and later releases.

Table 1: Minimum BIOS Versions Required

Server Name	BIOS Version
UCS-E160S-M3	2.x
UCS-E180D-M3 UCS-E1120D-M3	2.x
UCS-EN140N-M2	1.5.0.4

Minimum System Requirements

The management client must meet or exceed the following minimum system requirements:

- Sun JRE 1.6.0_14 or later
- Microsoft Internet Explorer 6.0 or higher, Mozilla Firefox 3.0 or higher
- Microsoft Windows 7, Microsoft Windows XP, Microsoft Windows Vista
- Apple Mac OS X v10.6, Red Hat Enterprise Linux 5.0 or higher operating systems

E-Series Server Options

E-Series Servers are available in the following options:

- Option 1—E-Series Server without preinstalled operating system or hypervisor
- Option 2—E-Series Server with preinstalled Microsoft Windows Server

At the time of purchase, you can choose the appropriate RAID option that you want enabled on the E-Series Server.



Note If you purchase this option, the Microsoft Windows Server license is preactivated.

- Option 3—E-Series Server with preinstalled VMware vSphere Hypervisor TM

At the time of purchase, you can choose the appropriate RAID option that you want enabled on the E-Series Server.

Cisco SD-WAN and SD-WAN IOS XE Support on UCS-E Series

Table 2: Cisco SD-WAN and SD-WAN IOS XE Release Compatibility

Cisco SD-WAN	SD-WAN IOS XE ISR4000	UCS-E Series using External Interfaces in SD-WAN mode	UCS-E Series using Internal Backplane Interfaces** in SD-WAN mode
19.2.x	16.12.1b and later releases	Supported	Not supported
20.1.1	17.2.1r	Supported	Limited feature support configurable using only Cisco vManage CLI templates



Note ** Interfaces - ucse x/y/0 and ucse x/y/1

For related information on Cisco SD-WAN and SD-WAN IOS XE support, refer to the [Compatibility Matrix](#) section in the Release Notes for Cisco IOS XE SD-WAN Devices, Cisco IOS XE Release Amsterdam 17.2.x

Cisco ISR G2, E-Series Server, NCE, and Cisco IOS Software Release Compatibility

Table 3: Cisco ISR G2, E-Series Server, NCE, and Cisco IOS Release Compatibility

Cisco ISR G2	Cisco IOS Software Release for Single-Wide E-Series Servers and the SM E-Series NCE	Cisco IOS Software Release for Double-Wide E-Series Servers	Cisco IOS Software Release for the EHWIC E-Series NCE
1921	—	—	15.4(3)M and later releases
1941	—	—	15.4(3)M and later releases
2911	15.2(4)M and later releases		15.4(3)M and later releases
2921	15.2(4)M and later releases	15.2(4)M and later releases	15.4(3)M and later releases
2951	15.2(4)M and later releases	15.2(4)M and later releases	15.4(3)M and later releases
3925	15.2(4)M and later releases	15.2(4)M and later releases	15.4(3)M and later releases
3925e	15.2(4)M and later releases	15.2(4)M and later releases	15.4(3)M and later releases
3945	15.2(4)M and later releases	15.2(4)M and later releases	15.4(3)M and later releases
3945e	15.2(4)M and later releases	15.2(4)M and later releases	15.4(3)M and later releases

Cisco ISR 4000 Series, E-Series Server, NCE, CIMC, and Cisco IOS Software Release Compatibility

Table 4: Cisco ISR 4000 Series, E-Series Server, NCE, CIMC, and Cisco IOS Release Compatibility

Cisco ISR	Cisco IOS Software Release for Single-Wide E-Series Servers and the SM E-Series NCE	Cisco IOS Software Release for Double-Wide E-Series Servers	Cisco IOS Software Release for the NIM E-Series NCE	CIMC
4400 Series	XE 3.12S	XE 3.12S	—	2.2.2 and later releases
	XE 3.13S and later releases	XE 3.13S and later releases	—	2.3.1 and later releases
	—	—	XE 3.15S and later releases	3.0.1 and later releases
	XE 16.2.1	XE 16.2.1	XE 16.2.1	3.0.1 and later releases
4300 Series	XE 3.13S and later releases	XE 3.13S and later releases	—	2.3.1 and later releases
	—	—	XE 3.15S and later releases	3.0.1 and later releases
	XE 16.2.1	XE 16.2.1	XE 16.2.1	3.0.1 and later releases

Important Information About the VMware FL-SRE-V-HOST License

If you are using a VMware FL-SRE-V-HOST license (equivalent to VMware vSphere Hypervisor™ 5.X), make sure that you are using 32 GB or less of RAM. If more than 32 GB of RAM is used, you will get an error message, and you will not be able to apply the license. If you want to use 48 GB RAM, upgrade your license to FL-SRE-V-HOSTVC.

Important Information About the Host Upgrade Utility

Since CIMC release 3.0.1, a separate Host Upgrade Utility User Guide is not supported. All the information that was present in the Host Upgrade Utility User Guide is merged into the [Getting Started Guide for Cisco UCS E-Series Servers and the Cisco UCS E-Series Network Compute Engine](#).

New Features for BIOS Releases UCSEM3_3.02 and UCSEDM3_3.02

This document provides new features, system requirements, compatibility information, and open and resolved caveats for the Cisco UCS E-Series Server and the Cisco UCS E-Series Network Compute Engine (NCE) software release 3.3.02. Use this document in conjunction with the documents in the [Related Documentation](#), on page 6.



Note Documentation is sometimes updated after original publication; therefore, for updated content, review the documentation on Cisco.com.

There are no new features in this release.

Resolved and Closed Bugs in BIOS Releases UCSEM3_3.02 and UCSEDM3_3.02

Table 5: Resolved or Closed Caveats

Bug ID	Summary
CSCvp73540	Enhance displaying GE ports in BIOS for PXE boot
CSCvs55018	ENCS5400: BIOS password change may not take effect if initiated from XMLAPI
CSCvs98599	BIOS password security & retention across BIOS upgrades for ENCS5400, UCS-E M3
CSCvv87924	BIOS password unable to be cleared
CSCvu69513	UEFI PXE boot: GE0, GE1 NIC's are not Detected in UCS-E M3 server module.
CSCvw07421	Evaluation of UCS-E M3 for Intel 2020.2 IPU
CSCvr93504	ERROR: Class:3000000; Subclass:50000; Operation: D

Open Bugs in BIOS Releases UCSEM3_3.02 and UCSEDM3_3.02

None

Related Documentation

For links to the following Cisco UCS E-Series Servers and the NCE documents, see Documentation Guide for Cisco UCS E-Series Servers and the Cisco UCS E-Series Network Compute Engine :

- [Getting Started Guide for Cisco UCS E-Series Servers and the Cisco UCS E-Series Network Compute Engine](#)
- [Cisco UCS E-Series Servers and the Cisco UCS E-Series Network Compute Engine Hardware Installation Guide](#)
- [Cisco Network Modules, Server Modules, and Interface Cards Regulatory Compliance and Safety Information](#)
- [GUI Configuration Guide for Cisco UCS E-Series Servers and the Cisco UCS E-Series Network Compute Engine Integrated Management Controller](#)
- [CLI Configuration Guide for Cisco UCS E-Series Servers and the Cisco UCS E-Series Network Compute Engine Integrated Management Controller](#)
- [CIMC XML API Programmer's Guide for Cisco UCS E-Series Servers and the Cisco UCS E-Series Network Compute Engine](#)
- [Troubleshooting Guide for Cisco UCS E-Series Servers and the Cisco UCS E-Series Network Compute Engine](#)
- [Open Source Used in Cisco UCS E-Series Servers and the Cisco UCS E-Series Network Compute Engine](#)
- Third-Party Tools Plug-In Documentation:
 - [Release Notes for Cisco IMC PowerTool](#)

- [Cisco UCS PowerTool Suite Installation and Configuration Guide](#)
- [Cisco IMC Remote Action Service 1.1.1 User Guide for HP Operations Orchestration 9.00](#)
- [Cisco IMC Smart Plugin 1.0 Installation Guide for HP Operations Manager—Windows](#)
- [Cisco IMC Smart Plugin 1.0 Operations Guide for HP Operations Manager—Windows](#)
- [Release Notes for Cisco IMC Management Pack, Release 1.1 for Microsoft System Center 2012, 2012 SP1 and 2012 R2, Operations Manager](#)
- [Cisco IMC Management Pack User Guide, Release 1.1 for Microsoft System Center 2012, 2012 SP1 and 2012 R2, Operations Manager](#)