

# Cisco ASR

## 9001ã, çã, °ãfªã, ²ãf¼ã, ·ãf§ãf³ã, µãf¼ãf“ã, ¹ãf«ãf¼ã, ¿ç” IOS

## XRã, ½ãf·ãf^ã, |ã, §ã, çã «ã Šã 'ã, <ãf·ãf©ã, °ãfjã



ã, çãf%ãfã, µã, ¶ãfªãf¼ã ID : cisco-sa-20160810-iosxr

[CVE-2016-6355](#)

ã^ã...-é-ã—¥ : 2016-08-10 16:00

æ€œæ>æ°æ—¥ : 2016-08-10 16:27

ãfãf¼ã, ãf§ãf³ 1.1 : Final

CVSSã, ¹ã, ³ã, ç : [7.8](#)

ã>žéç- : No workarounds available

Cisco ãfã, ° ID : [CSCux26791](#)

æ—¥æ-èªžã «ã, ^ã, <æf...ã ±ã -ã€ è<èªžã «ã, ^ã, <ãžÿæ-ãã ®éžã...-ã¼ã

æ!, è! ?

Cisco ASR 9001ã, çã, °ãfªã, ²ãf¼ã, ·ãf§ãf³ã, µãf¼ãf“ã, ¹ãf«ãf¼ã, ¿ç”ã ©Cisco IOS

XRã, ½ãf·ãf^ã, |ã, §ã, çã ©ãf%ãf©ã, µãfãã | çã tæ©ÿèf¼ã «ã Šã 'ã, <è,, tã¼±æ€§ã «ã, ^ã, Šã€è

ã “ã ©è,, tã¼±æ€§ã -ã€ è©²ã½”ãfãfãã, µã, ¹ã®ã |ã «é€ ä¿ãã ·ã, Æã, <ã€ã ·ãã |™ã «ç’ã

ã, ·ã, ¹ã, ³ã -ã “ã ©è,, tã¼±æ€§ã «ã ¾ãã |ã |ã™ã, <ã, ½ãf·ãf^ã, |ã, §ã, çã, çãffãf—ãfãf¼ãf^ã, 'ãfªãfªãf

ã “ã ©ã, çãf%ãfãã, µã, ¶ãfªã -æ-ãã ©ãfªãf³ã, -ã §çç°èªãããããã¾ã™ã€, <https://sec.cloudapps.cisco.com/security/center/content/CiscoSecurityAdvisory/cisco-sa-20160810-iosxr>

è©²ã½“è£¼ã” ?

è, †ã¼±æ€§ã ©ãã, ã, <è£¼ã” ?

ã “ã ©è,, tã¼±æ€§ã -ã€ Cisco ASR

9001ã, çã, °ãfªã, ²ãf¼ã, ·ãf§ãf³ã, µãf¼ãf“ã, ¹ãf«ãf¼ã, ¿ã, Šããããã½œã™ã, <ã€ Cisco IOS

XRã, ½ãf·ãf^ã, |ã, §ã, çãfªãfªãf¼ã, ¹5.1.xã€ 5.2.xã€ãã Šã, ^ã³5.3.xã€ «ã½±éÿã, 'ã, žã^ã¾ã™ã

ASR 9001, Cisco IOS

XR, show version, Cisco IOS XR

show version, Cisco IOS XR

### Cisco IOS XR Software

show version, Cisco IOS XR

XR, show version, Cisco IOS XR

show version, Cisco IOS XR

show version, Cisco IOS XR

### Cisco IOS XR Software

show version, Cisco IOS XR

show version, Cisco IOS XR

show version, Cisco IOS

XR, show version, Cisco ASR

9001, show version, Cisco

show version, Cisco

<#root>

RP/0/RSP0/CPU0:router#

show version

Cisco IOS XR Software, Version 5.1.3[Default]

Copyright (c) 2015 by Cisco Systems, Inc.

ROM: System Bootstrap, Version 2.04(20140227:092320) [ASR9K ROMMON],

router uptime is 2 days, 12 hours, 2 minutes

System image file is "bootflash:disk0/asr9k-os-mbi-5.1.3.sp7-1.0.0/0x100000/mbiasr9k-rp.vm"

cisco ASR9K Series (P4040) processor with 8388608K bytes of memory.

P4040 processor at 1500MHz, Revision 2.0

ASR-9001 Chassis

.  
.
.

è,,†á¼±æ€šã,'ã«ã,"ãšã,,ãªã,,ã"ã "ãÇç°èªã•ã,Œãÿè½á"  
ä»-ã®ã,ã,¹ã,³è½á"ã«ãšã,,ã!ã€ã"ã®ã,čãf%oãfã,ã,¶ã,¶ãfãã®ã½±éÿã,ã—ã  
IOS  
XRã,½ãf•ãf^ã,|ã,šã,čã®è,,†á¼±æ€šãŒã~ãœ"ã™ã,ãfªãfªãf¼ã,¹ã,ã®ÿè;Œã—ã|ã,,ã,ã,Ci  
ASR  
9001ã,čã,°ãfªã,²ãf¼ã,ãfšãf³ã,µãf¼ãf"ã,¹ãf«ãf¼ã,¿ã®ã¿ãšã,ã,ã"ã"ã,çç°èªã—ã

ã¾ãÿã€ã,ã,¹ã,³ã-ã€ã"ã®è,,†á¼±æ€šãŒCisco ASR 9006ã€ASR  
9010ã€ASR 9904ã€ASR 9910ã€ASR 9912ã€ã¾ãÿã-ASR  
9922ã,čã,°ãfªã,²ãf¼ã,ãfšãf³ã,µãf¼ãf"ã,¹ãf«ãf¼ã,¿ã«ã-ã½±éÿã,ã,Žã^ãªã,,ã"ã"ã,çç°èªã  
IOS XRã,½ãf•ãf^ã,|ã,šã,čã,ã®ÿè;Œã—ã|ã,,ã,ã,Cisco  
12000ã,ãfªãf¼ã,ãf«ãf¼ã,¿ã€Cisco Carrier Routing System(CRS)ã€Cisco Network  
Convergence System(NCS)6000ã,ãfªãf¼ã,°ãf«ãf¼ã,¿ã€Cisco NCS  
5000ã,ãfªãf¼ã,°ãf«ãf¼ã,¿ã€ã¾ãÿãÿã- Cisco NCS  
4000ã,ãfªãf¼ã,°ãf«ãf¼ã,¿ã«ã-ã½±éÿã,ã,Žã^ã¾ã>ã,"ã€,

### ã,»ã,ãfÿãfªãf†ã,£ã¾®³ã®ç—•è·j

ã"ã®è,,†á¼±æ€šãŒã,æfã^çç"ã•ã,Œã,ã"ã€è²á½"ãf†ãfã,ã,¹ã®RPã,šã®Softv  
Packet  
Path(SPP)ãf—ãfã,»ã,¹ãšãf;ãfçãfªãfªãf¼ã,-ãŒçç™ç"ÿã—ã€ãf†ãfã,ã,¹ãšãf«ãf¼ãf†ã,£ãf³ã  
çš¶æ...ãŒçç¶šãã-èf½æ€šãŒã,ã,šã¾ã™ã€,

ãf†ãfã,ã,¹ãŒã,æfã^çç"ã•ã,Œã,ã"ã€çç®çç†è€...ã-CLIã,ã½çç"ã—ã|RPã,šã®

<#root>

RP/0/RSP0/CPU0:router#

process restart spp location 0/rsp0/cpu0

Sun Jun 24 15:56:46.656 UTC  
RP/0/RSP0/CPU0: Jun 24 15:56:46.709 : sysmgr\_control[65747]: %OS-SYSMGR-4-PROC\_RESTART\_NAME : User root  
requested a restart of process spp at 0/RSP0/CPU0

ãžé



[http://www.cisco.com/c/ja\\_jp/support/web/tsd-cisco-worldwide-contacts.html](http://www.cisco.com/c/ja_jp/support/web/tsd-cisco-worldwide-contacts.html)

ç,,;â,,ÿã,çãffãf—ã,°ãf—ãf¼ãf%ã®ã³è±;è£½ã”ãSã,ã,ã”ã”ã,è¼æ~Žã—ã|ã,,ãÿã  
URL ã,ã”ç”æ,,ããããããã,ã€,

ä;®æ£æ,^ã;ãfãfãf¼ã,¹

ã”ã®è,,tä±æ€Sã—ã€Cisco ASR  
9001ã,çã,°ãfã,²ãf¼ã,ãfSãf³ã,μãf¼ãf”ã,¹ãf«ãf¼ã,¿ç”ã®Cisco IOS  
XRã,½ãfãfã,|ã,Sã,çãfãfãf¼ã,¹5.3.3ãSã;®æ£ãã,ã,£ã|ã,,ã¼ã™ã€,

ã”ã®è,,tä±æ€Sã—ã€Cisco IOS  
XRã,½ãfãfã,|ã,Sã,çã®æ¬ã®ã,½ãfãfã,|ã,Sã,çãfãf³ãftãfSãf³ã,¹ã,çãffãf—ãfãf¼ãf^(SMU)ãS

- asr9k-px-5.3.2.CSCux26791.piei¼^ãfãfãf¼ã,¹5.3.xç”¼%ã
- asr9k-px-5.2.4.CSCux26791.piei¼^ãfãfãf¼ã,¹5.2.xç”¼%ã
- asr9k-px-5.1.3.CSCux26791.piei¼^ãfãfãf¼ã,¹5.1.xç”¼%ã

Cisco IOS

XRã,½ãfãfã,|ã,§ã,çãfãfãf¼ã,¹6.0.xã—ã€ã”ã®è,,tä±æ€Sã®ã½±éÿã,ã—ã”ã”ã,,ã

ã”ã®ã,»ã,ã,ãfSãf³ã«ç”ã™ã,^ãtä«ã€é©ã^täãfãfãf¼ã,¹ã«ã,çãffãf—ã,°ãf—ãf¼ã

ä,æ£ã^©ç”ã°ã¼ã”ã...ã¼ç™è;”

Cisco Product Security Incident Response

Teami¼^PSIRTi¼%ã—ã€æœ—ã,çãf%ããfã,ã,¶ã,¶ãfãã«è”~è¼%ãã,ã,£ã|ã,,ã,è,,tä±æ€Sã

ã°ã...

ã”ã®è,,tä±æ€Sã—ã,μãfãf¼ãf^  
ã,±ãf¼ã,¹ã®è£æ±°ãã«ç™è|ãã,ã,£ã¼ã—ãÿã€,

URL

<https://sec.cloudapps.cisco.com/security/center/content/CiscoSecurityAdvisory/cisco-sa-20160810-iosxr>

æ”¹è,ã±ÿæ’

ãf◆ãf¼ã,ãfšãf³	èª-æ~Ž	ã,»ã,-ã,ãfšãf³	ã,¹ãf†ãf¼ã,¿ã,¹	æ—Yä»~
1.1	CVE IDã, 'è¿½ãŠ ã€,	Header	Final	2016ã¹'8æœ^10æ—Y
1.0	ã^◆ã>žã...-é-ãfªãfªãf¼ã,¹	-	Final	2016ã¹'8æœ^10æ—Y

## ã^©ç””è!◆ç´,,

æœ-ã, çãf%ãf◆ã,ªã, ¶ãfªã◆ç,,jã¿◆è"¼ã◆@ã,,ã◆@ã◆"ã◆—ã◆|ã◆"æ◆◆ã¾ã◆—ã◆|ã◆Šã,Šã€  
æœ-ã, çãf%ãf◆ã,ªã, ¶ãfªã◆@æf...ã ±ã◆Šã, ^ã◆³ãfªãf³ã, -ã◆@ã½¿ç""ã◆«é-çã◆™ã, <è²-ã»ã◆@ã, €  
ã◆¾ã◆Yã€◆ã, .ã, ¹ã, ³ã◆-æœ-ãf%ã,ãfªãfªãf³ã◆@ãt...ã@¹ã, 'ã^ã'Sã◆ªã◆—ã◆«ãª%ãæ'ã◆—ã◆  
æœ-ã, çãf%ãf◆ã,ªã, ¶ãfªã◆@è"~è¿°ãt...ã@¹ã◆«é-çã◆—ã◆|æf...ã ±é...◆ã¿jã◆@ URL  
ã, 'çœ◆ç•Yã◆—ã€◆ã◆~ç<-ã◆@è»çè¼%ã,,,æ,,◆è"³ã, 'æ-½ã◆—ã◆Yã 'ã◆^ã€◆ã½"çª¾ã◆CEç@jç◆  
ã◆"ã◆@ãf%ã,ãfªãfªãf³ãf^ã◆@æf...ã ±ã◆-ã€◆ã, .ã, ¹ã, ³è£½ã"◆ã◆@ã, "ãf³ãf%ãf|ãf¼ã, ¶ã, 'ã³¾è±;ã

## 翻訳について

シスコは世界中のユーザにそれぞれの言語でサポート コンテンツを提供するために、機械と人による翻訳を組み合わせて、本ドキュメントを翻訳しています。ただし、最高度の機械翻訳であっても、専門家による翻訳のような正確性は確保されません。シスコは、これら翻訳の正確性について法的責任を負いません。原典である英語版（リンクからアクセス可能）もあわせて参照することを推奨します。